

UF CORE

TYPE	FIG.	Dimensions(mm)					
		A	B	C	D	E	F
UF4/8/3/25	1	4.2±0.2	4.2±0.2	3.25±0.1/-0.15	1.35±0.25	1.4±0.1/-0.15	2.7±0.15
UF9.8/14/3	1	9.8±0.3	7.2±0.25	2.8±0.2	4.10min	2.8±0.2	4.4±0.25
UF10.5/16/5	1	10.5±0.35	7.9±0.25	5.0±0.3	5.20min	2.6±0.25	5.4±0.3
UF15/23/6	1	15.0±0.5	11.7±0.3	6.5±0.3	5.00min	5.1±0.3	5.9±0.3
UF15.7/20/6	1	15.9±0.3	10.0±0.2	5.9±0.2	6.80min	4.5±0.2	6.1±0.2
UF16/21/6	1	16.0±0.3	10.5±0.2	5.9±0.2	6.80min	4.5±0.2	6.5±0.35
UF16/54/10	1	16.2±0.3	27.0±0.3	10.0±0.20	7.2±0.3		22.5±0.2
UF19/36/6	1	19.7±0.4	18.0±0.5	6.0±0.3	7.40min	6.0±0.2	12.0±0.4
UF20/27/11	1	20.3±0.3	13.6±0.2	10.9±0.2	10.35min	4.9±0.2	8.7±0.3
UF21/32/7	1	21.4±0.5	15.9±0.3	7.3±0.3	6.00min	7.3±0.3	8.5±0.2
UF25/32/6	1	25.4±0.5	16.0±0.3	6.35±0.3	12.40min	6.35±0.3	9.65±0.2
UF27/58/10	1	27.2±0.3	29.0±0.3	10±0.3	14.2±0.3	6.5±0.2	22.5±0.3
UF31/43/7	1	30.5±0.6	21.8±0.4	6.7±0.3	12.0±0.4	11.8±0.4	10.0±0.4
UF31/38/14	1	31.0±0.5	19.1±0.2	13.85±0.2	19.0±0.5	6.0±0.3	13.1±0.3
UF33/27/7	1	33.0±0.5	13.5±0.2	7.2±0.2	18.00min	7.2±0.2	6.15±0.2
UF40/26/17	1	40.0±0.7	13.0±0.3	17.0±0.35	20.0±0.5	10.0±0.5	3.0±0.2
UF40/32/17	1	40.0±0.7	16.0±0.3	17.0±0.35	20.0±0.5	10.0±0.5	6.0±0.25
UF40/46/5	1	39.9±0.7	22.9±0.3	5.0±0.25	11.1±0.5	14.4±0.5	8.4±0.3
UF41/27/15	1	40.9±0.7	13.5±0.3	15.0±0.25	24.4±0.5	8.25±0.4	4.4±0.3
UF60/90/30	1	60.0±1.5	45.0±0.3	30.0±0.5	30min	15.0±0.5	30.0±0.3
UF64/128/40	1	64.0±1.5	64.0±0.5	40.0±0.5	24min	20.0±0.5	44.0±0.3
UF70/112/40	1	70.0±1.5	56.0±0.5	40.0±0.5	30min	20.0±0.5	36.0±0.3
UF72/84/28	1	72.0±0.8	42.0±0.5	28.0±0.5	44min	14.0±0.5	28.0±0.5
UF77/125/20	1	77.0±2.0/-1.0	62.5±0.5	20.0±0.4	37min	20.0±0.4	42.5±1.0/-0.5
UF80/160/40	1	80.0±1.5	80.0±0.5	40.0±0.4	39min	20.0±0.4	60±0.5
UF80/170/40	1	80.0±1.5	85.0±0.5	40.0±0.4	39min	20.0±0.4	65.0±0.5
UF86/86/28	1	85.0±3.0	43.5±0.5	28.0±0.7	56min	14.0±0.7	31.5±0.5
UF93/152/16	1	93.0±1.5	76.0±0.5	16.0±0.25	34.6min	28.0±0.3	48.0±0.5
UF93/152/30	1	93.0±1.8	76.0±0.5	30.0±0.5	34.6min	28.0±0.3	48.0±0.5
UF96/160/30	1	96.0±1.75	80.0±0.5	30.0±0.3	36min	30.0±0.5	49.0±0.5
UF100/160/40	1	100.0±1.5	80.0±0.5	40.0±0.3	60min	20.0±0.5	60.0±0.5
UF101/115/25	1	101.0±2	57.0±0.5	25.0±0.3	50.6min	25.0±0.5	32.0±0.5


UF CORE

FIG.1

Cl (mm ⁻¹)	Ae (mm ²)	Le (mm)	Ve (mm ³)	AL±25%(nH/N ²)			Weight g/PRS
				FW40	FW5K	FW10K	
3.79	4.75	18.03	85.74				0.4
4.3	7.9	34.2	271	450	980	2500	1.5
3.05	13	40	520	640	1400	2500	2.8
1.52	34.2	50.2	1719	1750			7.8
1.98	26	51.3	1330		2000	3300	6.8
2.12	23.3	51.7	1202	1000	2000	3600	8.0
2.6	118	45	5334		1250		13.0
2.29	35.3	81	2860		2400	3700	15.2
1.41	53.41	75.1	4055	930			22.0
1.27	54	68.6	3700	1800			19.0
2.09	40	83.7	3360		2600	4100	18.0
2.14	138.8	64.8	9001	1140			45.0
1.151	79.06	91.07	7200	2300			38.0
1.314	83.1	109.25	9079	2300			60.0
1.61	52.5	84.6	4440			4500	26.5
	170	83.4	14180	3800			71.0
	170	95.4	16220	3200			81.0
	72.5	101	7309.2	2000			37.0
	131.9	93.5	12332	2800			61.6
0.533	450	240	108000	4700			518.0
0.38	800	304	243200	6600			1167.0
0.335	800	284	227200	7000			1080.0
0.65	392	256	100352	4000			480.0
0.8	400	320	133000	3200			638.0
0.49	800	398	331040	5200			1580.0
0.522	800	418	341200	5000			1630.0
0.73	392	286	108276	3800			520.0
0.833	448	373	173030	3016			831.0
0.444	840	373	321432	5750			1557.0
0.444	900	390	354960	5800			1700.0
0.55	800	440	352000	4575			1680.0
0.527	625	328	206890	5000			992.0

UF CORE

TYPE	FIG.	Dimensions(mm)					
		A	B	C	D	E	F
UF105/190/40	1	105.0±2	95.0±0.5	40.0±0.3	45min	30.0±0.5	65.0±0.5
UF113/138/30	1	113.0±2	69.0±0.5	30.0±0.3	57min	28.0±0.5	40.0±0.5
UF115/188/28	1	115.0±2.5	94.0±0.75	28.0±0.5	51min	30.0±0.5	63.0±0.5
UF120/140/30	1	120.0±2.5	70.0±1	30.0±0.5	59min	30.0±0.5	40.0±0.5
UF120/160/40	1	120.0±2	80.0±0.5	40.0±0.5	58min	30.0±0.5	50.0±0.5
UF126/182/20	1	126.0±1.5	91.0±0.5	20.0±0.5	68min	28.0±0.5	63.0±0.5
UF130/182/40	1	130.0±2.5	91.0±0.5	40.0±0.5	68min	29.0±0.5	63.0±0.5
UF160/320/40	1	160.0±4	160.0±0.5	40.0±0.5	78min	40.0±0.5	120.0±0.5
UF240/320/40	1	240.0±5	160.0±0.5	40.0±0.5	160min	40.0±0.5	120.0±0.5
UF320/320/40	1	320±7/-5	160.0±1	40.0±0.5	240min	40.0±1	120.0±0.5

UI CORE

TYPE	FIG.	Dimensions(mm)					
		A	B	C	D	E	F
UI12.7/9/5	1	12.7±0.3	6.35±0.7	5.0±0.2	2.5±0.2	7.3min	3.8±0.4
UI25.4/22.6/6.35	1	25.4±0.5	16.25±0.3	6.35±0.3	6.35±0.3	12.4min	10.25±0.3
UI93/104/16	1	93.0±1.8	76.0±0.5	16.0±0.25	28.0±0.5	34.6min	48.0±0.5
UI93/104/30	1	93.0±1.8	76.0±0.5	28.0±0.5	30.0±0.3	34.6min	48.0±0.5
UI126/119/20	1	126.0±1.5	91.0±0.5	20.0±0.5	28.0±0.5	70min	63.0±0.5


UF CORE

FIG.1

Cl (mm ³)	Ae (mm ²)	Le (mm)	Ve (mm ³)	AL±25%(nH/N ²)			Weight g/PRS
				FW40	FW5K	FW10K	
0.391	1200	470	564000	6500			2700
0.462	840	390	331020	5500			1588
0.57	840	478	425432	4500			2042
0.445	899	400	362400	5650			1740
0.363	1200	436	536000	7000			2592
0.9	560	504	2822240	2800			1350
0.44	1160	504	593600	6000			2840
0.5	1600	800	1299200	5000			6236
0.6	1600	960	1536000	4200			7372
0.7	1600	1120	1792000	4100			8601


UI CORE

FIG.1

G	Cl (mm ³)	Ae (mm ²)	Le (mm)	Ve (mm ³)	AL±25%(nH/N ²)			Weight g/PRS
					FW40	FW44	FW95	
2.7±0.15	2.6	12.50	32.50	436		1000		2.70
6.35±0.3	1.65	38.90	64.30	2503		3100	3900	15.50
28.0±0.3	0.619	448.00	277.20	128179	4250			615.00
28.0±0.5	0.33	840.00	277.00	240336	7700			1150.00
28.0±0.5	0.67	560.00	378.00	211680	3750			1010.00